



# Fruit, vegetables, fish and flowers always perfectly fresh

The Italian-made humidification systems by Idrotech, Idrobase Group, are specially designed to preserve the freshness of food produce such as fruit, vegetables, fish and flowers. These systems prevent the dehydration of fresh products by means of filtered and sterilised water sprayed on the counters through nozzles arranged along a steel or Grilamid line.

Humidification prolongs the shelf-life of fruit, vegetables, fish and flowers by rehydrating them with an action that reduces their weight loss and also preserves their fresh appearance. Our misting systems help boost sales and reduce product weight loss by up to 50%.

# Products stay fresh much longer: to offer your customers products as fresh as just harvested from the field!

Our solution for limiting the financial loss caused by dehydration:

vegetables will lose between 15 and 58% of their weight, while fish will lose 12%. Humidification offers considerable advantages to retailers: it reduces the weight loss of these products up to 90% and prolongs their freshness

Refrigerated counters, non-refrigerated display cases, and storehouses are all low-humidity environments (50-60%). This causes the rapid deterioration of most fruit and vegetables, which

lose weight, change colour and take on an uninviting appearance.

On the contrary, correctly humidified products will look <u>just harvested</u>, with <u>moist, firm and fresh surfaces</u>. To maintain the right humidity level as long as possible during display and storage.

Our humidification system is fully automatic: it features great versatility and extremely low operating costs.





To understand how much you can save, let's examine the produce department of a supermarket:

- Daily sales= **€ 500**
- Without Idrobase Group **humidification**: losses due to weight loss or deterioration **8%**= **€40**
- With Idrobase Group **humidification**: losses due to weight loss or deterioration **4%**= **€20**
- Daily savings= **€ 20**
- Annual savings: € 20 x 300 working days = € 6000





## We keep your supermarket products in great shape

	Typical daily weight loss	Daily weight loss with Humi Fog / Humi Extra	Reduction in weight loss	Change in appearance
Artichoke	4.05%	0.58%	85.68%	***
Avocados	0.38%	0.08%	79.62%	*
Broccoli	7.55%	0.75%	90.07%	**
Brussels sprouts	3.47%	1.54%	55.62%	***
Cabbage	1.39%	0.28%	79.86%	***
carrots	4.65%	1.61%	65.38%	**
Cauliflower	2.04%	0.41%	79.90%	***
Celery	3.08%	1.29%	58.12%	**
Grpfruit	0.64%	0.21%	67.19%	***
Grp	1.46%	0.73%	50.00%	***
Lemons	1.17%	0.36%	69.23%	*
Lettuce	7.05%	0.92%	86.95%	***
Mshroom	12.06%	5.90%	51.04%	***
Lg mushroom	12.09%	4.58%	62.10%	***
Oranges	0.45%	0.22%	51.11%	*
Peaches	3.38%	2.23%	34.09%	***
Plums	0.83%	0.41%	49.79%	***
Radishes	5.88%	2.94%	50.00%	***
Strberry	2.43%	1.11%	54.23%	**
Tomatoes	0.23%	0.07%	69. 30%	*





## Carefree humidification




If you decide to use **our humidification system** in your store, **Idrotech** will **design** the most functional system, ensure perfect **installation** and carry out **maintenance**, to guarantee all the **benefits of humidification**, a **successful outcome** and **maximum user-friendliness**.




### The benefits are clear

The following graphs compare 5°C refrigerated environments that are not humidified with others that are humidified. (Considering products kept at an **ideal degree of humidification**). Humi Fog and Humi Extra allow for **perfect rehydration**, therefore, the **benefit** derived from using this system will be **substantially greater** than that indicated by the graphs.







with Humi Fog and Humi Extra

without Humi Fog and Humi Extra

## Why you should choose our humidification:



Greater economic savings, **50% savings** compared to the average competing systems on the market



Minimum footprint: **50x50x15cm** 

80%

**80% less** maintenance compared to other systems



**Perfect Electronic antidrip system**, to prevent unpleasant dripping

1h

Installation takes about **1 hour,** instead of the 3 hours of other systems



Built-in **sterilisation system** to guarantee sanitised water

125

Low energy consumption, 125W compared to other systems which require 800W



Humidification keeps away annoying and anti-hygienic flying insects

# DROBASE ASSION FOR WATER

# Humidification kit in supermarkets



The solution to ensure humidification in supermarkets

The humidification kit in supermarkets includes several solutions:

Humidification Kit for supermarkets



**Humi Fog**: medium pressure humidification system for **small areas** in supermarkets

Fog Extra to cool, humidify, suppress dust and odours and many more



# High pressure

# **Humi Extra**











# Medium pressure fog 230V-50Hz



Water inlet filter as standard, with 80micron AISI 304 stainless steel mesh. Works in conjunction with IT.0581 water supply Kit



Easy to use



Silent working



Pump free of maintenance





**Humi Fog** is a humidification system specially designed to preserve the freshness of fruit, vegetables, fish and flowers. The nebulised water, **filtered** and **sterilised**, which is sprayed on the counters through nozzles arranged along a steel or polyamide line, rehydrates the food produce, preventing **dehydration** and reducing **weight loss**.

ij.	H
	N W
	Ž.
<b>E</b>	SS
	Æ

Humi Fog			compatibility with Humidification kit		
		Description	3m	6m	
	ZX.HF	<b>Module Humi Fog,</b> 25I/h, 25bar, 125W, 230V-50Hz (complete with sterilising lamp)	•	•	

			in metres
		3m	6m
Humidification kit	Description	ZX.KH3	ZX.KH6
	Polyamide pipe for high pressures Ø6.35mm, (in metres)	25	25
www.educanducan	<b>AISI 304 stainless steel pipe</b> ø12mm 3000mm, 6 holes, pitch 500mm, complete with adjustable threaded adapters 10/24UNC/2A	1	2
35	<b>Rubberised stainless steel pipe clamp</b> for fixing a polyamide pipe, Ø6.35mm	35	35
	<b>Pipe junction Slip-Lock quick coupling,</b> straight, made of AISI 303 stainless steel for Ø12mm pipes	-	1
	End of line cap Slip-Lock - in AISI 303 stainless steel for Slip-Lock ø12mm	1	1
	<b>Pipe junction Slip-Lock quick coupling,</b> straight, made of AISI 303 stainless steel, adapts from 12mm to Ø6.35mm	1	1
<b>a</b>	<b>Fog nozzle in nickel-plated brass,</b> cleanable, complete with anti-drip valve, 10/24UNC/2A thread, flow factor 015	6	12
>	<b>Tube cutter</b> for polyamide pipe ø2-12mm	1	1

#### Recommended accessories



IT.0581

Water supply kit complete with mesh filter, and Fog module 3m water connection pipe



0582

**Anti-limescale filter** with polyphosphate salts for water supply kit

#### Technical features

- Voltage 230V-50Hz
- · Water filter with SS cartridge
- · Thermal protection fuse
- · UV lamp 300
- $\cdot$  Power absorbed (module+UV lamp) 125W
- Pump dimensions 42x20x32cm
- L.p. Slip-Lock inlet ø9.6mm
- Outlet, Slip-Lock ø6.35mm

### Adjustable timer:

- Work from 1 to 60 sec
- Pause from 1 to 60 min
- The system usually works according to a pause/work cycle, nebulising for a few seconds every 5-10 minutes, thus making actual consumption very low

#### Humi Fog consumption:

- · 125W working
- 12W stand-by













# Fog kit 60bar 230V-50Hz



Fog Extra to cool, humidify, suppress dust and odours and many more



Humidification kit for Supermarket



Water inlet filter as standard, with 80micron AISI 304 stainless steel mesh. Works in conjunction with IT.0581 water supply Kit



Detail of the sterilising lamp

#### **NEW SAFETY SYSTEM:**

in the event of a pipe break in the fog nozzle lines, the system automatically shuts down to prevent flooding of the areas where the lines are installed

# The perfect degree of humidification to preserve the freshness of fruit, vegetables, fish and flowers

**Humi Extra** is a humidification system specially developed to preserve the freshness of fruit, vegetables, fish and flowers. The nebulised water, filtered and sterilised, which is sprayed on the counters through nozzles arranged along a steel or polyamide line, rehydrates the food produce, preventing dehydration and reducing weight loss. The new control panel allows for quick and accurate setting of the work times and management of the connected optional probes.



Programmer (weekly)



Desired humidity (settable)



Keeps insects away

0	- Optionals
X	- Not available

ZX.KM-EC	Maintenance kit 2 piston axial pump (valve kit and water seals kit for pump)	0	0	0	X	X	X
ZX.KM-AX	Maintenance kit 3 piston axial pump (valve kit and water seal kit for pump)	X	X	X	0	0	0
IT.0915	UV lamp 300	0	0	0	0	0	0
ZX.SU20	Moisture Probe for Fog Extra - 20m cable	0	0	0	0	0	0



			_	•				
Humi Extra		Description	compatibility with Humidification kit					
			3m	6m	9m	12m	15m	18m
	ZX.HE-O5	Fog Extra 0.5I/min 60bar complete with sterilising lamp	•					
	ZX.HE-1	Fog Extra 11/min 60bar complete with sterilising lamp		•	•			
	ZX.HE-2	Fog Extra 21/min 60bar complete with sterilising lamp				•	•	•

line	length	in	metres
------	--------	----	--------

	inte length in the						
		3m	6m	9m	12m	15m	18m
Humidification kit	Description	ZX.KH3	2Х.КН6	2Х.КН9	ZX.KH12	ZX.KH15	ZX.KH18
	<b>Polyamide pipe</b> for high pressures, ø6.35mm (in metres)	25	25	25	25	25	25
85	<b>Rubberised stainless steel pipe clamp</b> for polyamide pipe fixing Ø6.35mm	35	35	45	45	55	65
whomeworkersenselings	AISI 304 stainless steel pipe Ø12mm 3000mm, 6 holes, pitch 500mm complete with adjustable threaded adapters 10/24UNC/2A	1	2	3	4	5	6
	<b>Pipe junction Slip-Lock quick coupling,</b> straight, made of AISI 303 stainless steel for Ø12mm pipes	-	1	2	3	4	5
	<b>Pipe quick coupling, "Tee",</b> in nickel-plated brass, Ø6.35mm	-	-	1	1	1	1
	End of line cap Slip-Lock in AISI 303 stainless steel for Slip-Lock Ø12mm	1	1	2	2	2	2
	<b>Pipe junction Slip-Lock quick coupling,</b> straight, made of AISI 303 stainless steel, adapts from 12mm to Ø6.35mm	1	1	2	2	2	2
200	<b>Tube cutter</b> for polyamide pipe Ø2-12mm	1	1	1	1	1	1
<	Fog nozzle in nickel-plated brass, complete with anti-drip valve and cleanable 50micron mesh filter, 10/24UNC/2A thread, flow factor 015	6	12	18	24	30	36

#### Recommended accessories



#### **Technical features**

- Frame in painted steel sheet
- **Electric pump** 1450rpm, 230V-50Hz
- · Unloader valve
- Low pressure solenoid valve 230V-50Hz, water inlet
- **High pressure solenoid valve** 230V-50Hz, to discharge line pressure
- Electrical panel complete with: ON/OFF thermal cutout, electronic board for management of anti-drip and timer system
- · Dimensions WxLxH: 600 x 300 x 300mm
- · Slip-lock inlet ø9.6mm
- Outlet, Slip-Lock ø6.35mm
- **High pressure switch** for no water supply and pipe breaks
- Dimensions WxLxH:  $600 \times 300 \times 300 \text{mm}$







#### \*TERMS OF SUPPLY

- Delivery: EX WORKS
- Packing: NOT INCLUDED
- Our prices are quoted excluding VAT
- Specifications, data, tables and illustrations are provided for guidance only. Idrobase Group s.r.l. reserves the right to make changes without prior notice.
- The list prices will be reviewed monthly and may be subject to changes due to continuous market fluctuations.



idro**base**°

Innovative pressure

idrobase.it



club dei riparatori\*

The winning solution to manufacture and repair all kinds of pressure washers

clubdeiriparatori.it



Enjoy your life Night & Day

enjoyyourfurniture.com



idro**tech**'

Tailor-made misting systems

idrotech.com



The winning solution to manufacture and repair all kinds of misting systems

clubdelmisting.com

#### Idrobase Group s.r.l.

35010 BORGORICCO (PD) ITALIA - Via dell'Industria, 25





info@idrobasegroup.com

www.idrobasegroup.com







